



**28W LED Driver with 1400mA Constant Current
PDA028A LED Power Supply for Residential Lighting**



Features

- Constant Current
- OVP, OCP, Short/Open Circuit Protection
- IP66 Rating
- UL8750 Compliant
- SELV Compliant
- Brownout/Brownout Recovery
- Low Profile Design

Applications

- Indoor Lighting
- Architectural Lighting

Safety Approvals

- cUL/UL

Mechanical Characteristics

- Length: 80mm (3.15in)
- Width: 78mm (3.07in)
- Height: 25.4mm (1.00in)
- Weight: 215g (7.58oz)

Output Specifications

Model	Output Current	DC Output Voltage Range			Max Power
		Min.	Typ.	Max.	
PDA028A-1A4B-R	1400mA	14V	-	20V	28W

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

INPUT:

AC Input Voltage
108 to 132VAC

Nominal AC Input Voltage
120VAC

Leakage Current
0.5mA maximum at 110VAC

Maximum Input Current
500mA (RMS) at 108VAC

Inrush Current
<30A at 132VAC, 60Hz

OUTPUT:
Output Power
28W

Efficiency
80% minimum at full load, nominal AC input

Power Factor
≥0.9 at full load, nominal AC input

Turn-on/off Delay Time
0.5ms maximum at nominal AC power on

ENVIRONMENTAL:

Operating Temperature -40 to +40°C
Storage Temperature -40 to +85°C

Operating Humidity 10 to 95%
Storage Humidity 05 to 95%

Warranty
3 Years

Ingression Protection
IP66

EMC

FCC Part 15 Class B

Immunity

IEC61000-4-2
IEC61000-4-3
IEC61000-4-4
IEC61000-4-5
IEC61000-4-8
IEC61000-4-11

Isolation Test (HI-POT)

Primary to secondary: 2000VAC for 1 minute,
10mA

Insulation Resistance

Primary to secondary: >5M OHM 500VDC, 1
minute

FEATURES:**Input Over Current Protection**

The input power line will be fused with a 1A fuse

Short Circuit Protection

The Driver will withstand a short circuit across the
outputs without damage

Output Over Voltage Protection

During no load condition, the over voltage
protection trigger level is <35V.

Lifetime

10K Hours minimum (Tc <80°C)

Input / Output Wires (Solid or Stranded)

Position	Terminal Color	Specification
Line	Black	AWG18
Neutral	White	AWG18
Vout+	Red	AWG18
Vout-	Black	AWG18

