



## 125W Constant Voltage LED Driver PDA125 Series for Outdoor Lighting



### Features

- High Efficiency
- UL8750 Compliant
- 5 Year Warranty
- OVP, Short and Open Circuit Protection
- IP66, Potted
- 120V-277VAC Rated Operation
- Brownout/Brownout Recovery
- Class 2 per UL1310

### Applications

- General Lighting
- Street Lighting
- Outdoor Lighting
- Architectural Lighting

### Safety Approvals

- CE
- cUL/UL

### Mechanical Characteristics

- Length: 194mm (7.64in)
- Width: 68mm (2.67in)
- Height: 37mm (1.46in)
- Weight: 936g (2.06lbs)

### Output Specifications

Model	DC Output Voltage	Output Current			Output Power <sup>(1)</sup>
		Min.	Typ.	Max.	
PDA125X-24VF	24V	0mA	-	5.2A	125W
PDA125X-48VF	48V	0mA	-	2.6A	125W

Note (1): Output power drops to 112.5W maximum when input is 90-100VAC  
 (2): Substitute W for X when ordering dimming version and B for non-dimmable model.

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**Input:**

**AC Input Voltage Range**

90VAC to 304VAC

**AC Input Frequency**

47~63Hz

**Maximum Input Current**

≤ 2A

**Leakage Current**

0.5mA maximum at 230VAC Input

**Inrush Current**

≤ 30A

**OUTPUT:**

**Power Factor**

≥ 0.9

**Ripple and Noise**

<35% (p-p)

**Efficiency**

93% at 230~ 277VAC

91% at 120VAC

**Turn-on Delay Time**

0.5s maximum at nominal AC Power ON

**Environmental:**

**Temperature**

Operation -40 to +60°C

Non-operation -40 to +85°C

Operating Humidity 10 to 95%

**Dimming Function: (W Models)**

**Dimming Control**

0-10VDC

**Dimming Output to Load**

PWM at 1000Hz

**Dimming Grounding**

Dim(-) and Vout(-) must never be connected together to ensure proper operation and isolation requirements

**EMC**

EN55015/CISPR 15/FCC 47 Part 15/18 Class A

**Immunity**

IEC61000-4-2

IEC61000-4-3

IEC61000-4-4

IEC61000-4-5

IEC61000-4-6

IEC61000-4-8

IEC61000-4-11

IEC61000-3-2 Class C

**Input Over Current Protection**

The input power line will be fused with a 2A fuse

**Short-Circuit Protection**

The PSU will withstand a short circuit across the outputs without damage

**Open Circuit Protection**

Once the circuit is opened, the output voltage should be less than 120% at nominal AC input conditions

**Dielectric Withstand (Hi-pot) Test**

Primary to secondary: 4242VDC for 1 minute, 5.5mA

**Insulation Resistance**

Primary to secondary: >5M Ohm 500VDC, 1 Minute

**Lifespan**

50K Hours at full output power, 50°C ambient, Tcase < rating

**Wire Connections**

Position	Terminal Color	Specification
Line	Black	AWG18 Solid Wire
Neutral	White	AWG18 Solid Wire
Ground	Green/Yellow	AWG18 Solid Wire
Vout+	Red	AWG18 Solid Wire
Vout-	Blue	AWG18 Solid Wire
Dim+	Violet	AWG18 Solid Wire
Dim-	Grey	AWG18 Solid Wire

**Warranty**

5 Years

