



## 30W Single Port Power over Ethernet Midspan IEEE802.3at Compliant Power Injector



### Features

- Compliant with IEEE802.3at Standard
- Non-vented Case
- Full Protection OVP, OCP
- 1 year warranty
- Limited Power Source
- Gigabit Compatible
- May power Cisco AP1250 with ACCY125X dongle

### Applications

- IP Telephones
- Wireless Access Points
- Bluetooth® Access Points
- Security Cameras
- IP Print Servers
- WiMAX® Access Points

### Safety Approvals

- CE
- cUL/US

### Mechanical Characteristics

- Length: 140mm (5.51in.)
- Width: 65mm (2.55in.)
- Height: 36mm (1.42in.)
- Weight: 0.2Kg (7.58oz)

### Output Specifications

Model	AC Input	DC Output Voltage	Load		Regulation	
			Min.	Max.	Line	Load
POE31U-1AT <sup>1</sup>	Three Wire	56V	10mA	535mA	±5%	
POE31W-1AT <sup>1</sup>	Two Wire	56V	10mA	535mA	±5%	

Notes: (1) Consult factory for availability

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**INPUT:**

**AC Input Voltage Rating**  
100 to 240VAC

**AC Input Voltage Range**  
90 to 264VAC

**AC Input Current**  
0.8A (RMS) maximum at 120VAC  
0.55A (RMS) maximum at 240VAC

**AC Input Frequency**  
47 to 63Hz

**Leakage Current**  
350uA maximum for U models  
250uA maximum for W models

**Max In-rush Current**  
60A maximum at 240VAC and maximum load (Cold Start at ambient 25°C)

**OUTPUT:**

**Output Power**  
30W

**Hold up Time**  
10mSec min at max load at 120VAC, 60Hz

**Transient O/P Voltage Protection**  
60V max at switch on/off at any AC line phase

**Efficiency**  
80% Typical at max load at 120VAC, 60Hz

**Environment**

Operating Temperature	0 to +40°C
Non-operating Temperature	-20 to +65°C
Relative Humidity	5 to 90%

**EMI**

EN55022 Class B  
FCC part 15 Class B

**EMC**

ESD:	IEC61000-4-2	Level 3
RS:	IEC61000-4-3	Level 3
EFT/Burst:	IEC61000-4-4	Level 2
Surge:	IEC61000-4-5	Level 3
CS:	IEC61000-4-6	Level 3
Voltage Dips:	IEC61000-4-11	
Harmonic:	IEC61000-3-2	Class A

**Isolation (HI-POT)**

Primary to secondary: 1500VAC for 1 minute, 10mA

**Insulation Resistance**

Primary to secondary: 10M Ohm 500VDC

**FEATURES:****Over Voltage/Current, Short Circuit Protection**

The output is equipped with short-circuit protection and overload protection as per the IEEE 802.3at specification and conforms to UL60950-2. The output can be shorted permanently without damage.

**Indicator**

Solid Green: Valid IEEE802.3at load detected and connected "ON"  
Blinking Green: Power "ON" ready for connection  
Blinking Red/Green: Invalid load connected  
Blinking Red: fault

**AC Input Connector**

IEC320 C14 - U Models – three wire  
IEC320 C8 – W Models – two wire

**Output Connection**

+pins 3,6 / -pins 1,2

**Data IN/POE OUT Connector**

RJ45

**Warranty**

1 year

**Dimension Diagram Unit: mm**

