



8 Port Gigabit Power over Ethernet Midspan POE370U for 10/100/1000 Base-T Networks



Features

- IEEE 802.3af Detection, Disconnect and Overload Protection
- NIC Interface (Optional)
- SSL Option with SNMPv3
- 10/100/1000 base T Compatible
- Limited Lifetime Warranty
- Full Power of 370W--15.4W per Port No Power Management required
- Full Protection OTP, OCP, OVP
- 48V RPS Input (Optional)
- Cisco Legacy Detection
- 1U Rack Mounting Kit Ships with Unit

Applications

- VoIP Phones
- Access Point
- Security Systems
- Lighting Systems with Single UPS

Safety Approvals

- cUL/UL
- CE
- SAA
- C-Tick

Mechanical Characteristics

- Length: 438mm (17.25in)
- Width: 228mm (8.98in)
- Height: 44.5 mm (1.75in)
- Weight: 3.8Kg (8.5lbs)

Output Specifications

Model	Number of Ports	Maximum Output Power
POE370U-480-8	8	125W
POE370U-480-8-N	8	125W

Notes: (1) "N" includes SNMP, Simple Network Management Protocol

Reference Files:

1. [Multiport Midspan Installation Manual.pdf](#)
2. [19in Rack Mounting Kit Datasheet.pdf](#)
3. [SNMPv2c User Manual-Rev1.7.pdf](#)
4. [SNMPv2c Firmware-Rev1.7.zip](#)
5. [SNMPv2c MIB 10 30 2009.zip](#)

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

INPUT:**AC Input Voltage Range**

90 to 264VAC

AC Input Voltage Rating

100 to 240VAC

AC Input Current

5.5A (RMS) maximum for 90VAC

2.75A (RMS) maximum for 240VAC

Leakage Current

3.5mA maximum @ 254VAC 60Hz

AC Input Frequency

47-63Hz

AC Inrush Current

30A (RMS) maximum for 115VAC

60A (RMS) maximum for 230VAC

OUTPUT:**Total Output Power**

15.4W per port

Ripple and Regulation

100mV maximum

Efficiency75% (typical) at maximum load, and
120VAC 60Hz**Hold-up Time**

16mS min. 120VAC at maximum load

Transient O/P Voltage Protection60V maximum at switch on and off at any
AC line Phase**Turn-On Delay Time**3 sec maximum at maximum load, and
120VAC 60Hz, 25Hz**ENVIRONMENTAL:****Temperature**

Operation 0 to +40°C

Non-operation -25 to +65°C

Humidity 5 to 90%

EMCEn55022 Class B, FCC Class B with FTP
cablingEN55022 Class A, FCC Class A with UTP
cabling**Isolation Test**Primary to Secondary: 4242VDC for 1
minute

Primary to Ground: 2121VDC for 1 minute

Secondary to Ground: 2121VDC for 1
minute**Immunity EN50082-1**

ESD: EN61000-4-2. Level 3

RS: EN61000-4-3. Level 2

EFT: EN61000-4-4. Level 2

Surge: EN61000-4-5. Level 3

CS: EN61000-4-6. Level 2

Voltage Dips EN61000-4-11

Harmonic: EN61000-3-2 Class A

IEEE 802.3af InteroperabilityUNH Interoperability report available on
request**FEATURES:****Cisco Legacy detection**

No extern parts required for Legacy devices:

VoIP Phones:

7910, 7912, 7940, 7960

Access Points:

350, 1100, 1200

**Over Voltage/Current, Short Circuit
Protection**The output can be shorted permanently
without damage

Over Temperature Protection

Automatic shutdown without damage

Indicators

Green LED: Power detected “ON”

Yellow LED: Fault detected

USB Diagnostics Port

USB “B” port for diagnostics and manual port control

Windows GUI

Input Connector

AC

IEC320 inlet 3 pin

DC for RPS option

Molex Minifit

Shell 39-01-20-65

Pins 39-00-0077

POE370U-480-8 Dimension Diagram Unit: mm

