



## 8-Port 72W per Port Midspan POE576U-8UP-N for 10/100/1000 Base-T Networks



### Features

- Proprietary Detection, Disconnect and Overload Protection
- Limited Power Source
- Gigabit Compatible
- 1U Rack Mounting Kit Ships with Unit
- SNMPv2c Management
- Full Power of 576W--72W per Port
- Full Protection OTP, OCP, OVP
- Ultra PoE at 72W per port
- 1 Year Warranty

### Applications

- Wireless Access Points
- Computer Workstations
- Security Systems
- IP Cameras

### Safety Approvals

- cUL/UL
- CE

### Mechanical Characteristics

- Length: 438mm (17.25in)
- Width: 228mm (8.98in)
- Height: 44.5 mm (1.75in)
- Weight: 3.8Kg (8.5lbs)

### Output Specifications

| Model <sup>(1)</sup> | DC Output Voltage | Load |                     | Output Power per Port |
|----------------------|-------------------|------|---------------------|-----------------------|
|                      |                   | Min. | Max. <sup>(2)</sup> |                       |
| POE576U-8UP-N        | 56V               | 15mA | 1.29A               | 72W                   |

Note (1): Model without SNMP management available upon special request

Note (2): Max load applies to compliant load at 12.5K detection. If operating at 25K “IEEE802.3at mode” max load is 0.6A

Reference files:

1. [SNMPv2c\\_User\\_Manual-Rev1.7.pdf](#)
2. [Multiport\\_Midspan\\_Installation\\_Manual.pdf](#)
3. [SNMPv2c\\_Firmware-Rev1.7.zip](#)
4. [SNMPv2c\\_MIB\\_10\\_30\\_2009.zip](#)

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**INPUT:****Input Voltage Rating**

100 to 240VAC

**Input Voltage Range**

90 to 264VAC

**AC Input Current**

9.0A (RMS) 90VAC at maximum load

4.25A (RMS) 230VAC at maximum load

**AC Input Frequency**

47 to 63Hz

**Leakage Current**

3.5mA maximum at 264VAC and 60Hz

**Max In-Rush Current:**

30A for 115VAC at maximum load

60A for 230VAC at Maximum load

(Cold Start at Ambient 25°C)

**OUTPUT:****Total Output Power**

72W per port

576W Maximum Total Power

**Ripple and Regulation**

250mV maximum

**Efficiency**

75% (typical) at maximum load, and

120VAC 60Hz

**Hold-Up Time**

16mS min. 120VAC and maximum load

**Transient O/P Voltage Protection**

60V maximum at switch on and off at any

AC line Phase

**Turn-On Delay Time**

20 sec maximum at maximum load,

120VAC 60Hz

**ENVIRONMENTAL****Temperature**

Operation 0 to +40C

Non-Operation -25 to +65C

Humidity 5 to 90%

**EMC**

EN55022 Class A, FCC Class A with UTP cabling

EN55022 Class B, FCC Class B with FTP cabling

**Isolation Test**

Primary to Secondary: 4242VDC for 1 minute

Primary to Ground: 2121VDC for 1 minute

Secondary to Ground: 2121VDC for 1 minute

**Immunity EN50082-1**

ESD: EN61000-4-2 Level 3

RS: EN61000-4-3 Level 2

EFP: EN61000-4-4 Level 2

Surge: EN61000-4-5 Level 3

CS: EN61000-4-6 Level 2

Voltage Dips: EN61000-4-11

Harmonic: EN61000-3-2 Class A

**IEEE802.3af/at Interoperability**

If 25K Ohm is detect the unit operates in "IEEE802.3at mode" 33.6W 2 pair powering. 12.5K detection resistance required for full power.

**FEATURES:****Cisco Legacy Detection**

No extern parts required for Legacy

Devices:

VoIP Phones:7910, 7912, 7940, 7960

Access Points350, 1100, 1200

**Over-Voltage/Current, Short Circuit Protection**

The output can be shorted permanently without damage

**Over Temperature Protection**

Automatic shutdown without damage

**Indicators**

Solid Green LED: Power detected “ON”

Flashing Green: IEEE802.3at or (af) detected

Yellow LED: Fault detected

**Input Connector**

AC Input IEC320 C14

**Output Connection**

4-pair powering for full power

Pins 3,6, 4,5(+)

Pins 1,2, 7,8 (-)

2-pair powering for IEEE802.3at mode

Pins 3,6(+)

Pins 1,2 (-)

**SNMPv2c management port Interface**

NIC interface for remote management via secure IP access

**POE576U-8UPN Dimension Diagram**

