

Keyway Testing Technology (Guangdong) Co., Ltd. Room 2102, Building 6, Dongyi Intelligent Equipment NewEnergy Vehicle Park, No.30 of Tangxia District, Dongshen Road, TangxiaTown, Dongguan City, Guangdong province, China Tel : 86-769-87182258 Fal : 86-769-87181058

Mail : kwtest@keywaytest.com

Certificate of Conformity

No. CA24070784-S-000

The following products have been tested by us with the listed standards and found in Conformity with the council LVD directive 2014/35/EU. It is possible to use CE marking to demonstrative the Conformity with this LVD Directive. (Type Examination Certificate).

Applicant	: Phihong Technology Co., Ltd.
Address	: No. 568, Fuxing 3rd Rd., Guishan District, Taoyuan City 333, Taiwan
Product	: SWITCHING POWER SUPPLY
Trade Name	: PHHONG
Model No.	: PYA10xyzzzppp, PYA12xyzzzppp, PYA15xyzzzppp, PYA10xyzzzpppQ, PYA12xyzzzpppQ, PYA15xyzzzpppQ ("x", "y", "zzz" and "ppp" are variables, see Table A for
	details)

Te	est Standards :
EN IEC 62368-1:2020 + A11:2020	Audio/video, information and communication technology equipment Part 1: Safety requirements

Table A: Definition of variables:

Variable:	Range of variable:	Content:
Х	E, K, T	Indicating one digit number to represent
		different plug type:
		E denotes European plug
		K denotes United Kingdom plug
		T denotes detachable plug, only for
		horizontal type enclosure
У	V or blank	Represents different shell type:
		V denotes vertical
		blank denotes Horizontal
ZZZ	050 to 300	'zzz' are 3 digits indicating 10 times the
		output voltage value in V. For example,
		050 represents the output voltage is
		5.0Vdc, 300 represents the output voltage
		is 30.0Vdc.
ррр	001 to 300	'ppp' are 3 digit <mark>s indicating</mark> 100 times the
		output current value in A. For example,
		001 represents the output current is
Remarks:		0.01A, 300 represents the output current is 3.0A.
The rated The rated Output vol power. The detac	output current is rising in steps of output voltage is rising in steps of tage multiplied with output curre hable plug portion can be Europ = "T", "y" can only be "blank".	0.01A, 300 represents the output current is 3.0A. of 0.01A. of 0.1V. nt are only tested up to the maximum output
The rated The rated Output vol power. The detac	output voltage is rising in steps of tage multiplied with output curre hable plug portion can be Europ	0.01A, 300 represents the output current is 3.0A. of 0.01A. of 0.1V. nt are only tested up to the maximum output

The statement is based on a single evaluation of one sample of above mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab. logo.