



Keyway Testing Technology (Guangdong) Co., Ltd.
Room 2102, Building 6, Dongyi Intelligent Equipment
NewEnergy Vehicle Park, No.30 of Tangxia District,
Dongshen Road, TangxiaTown, Dongguan City,
Guangdong province, China

Tel : 86-769-87182258

Fal : 86-769-87181058

Mail : kwtest@keywaytest.com

Certificate of Conformity

No. CA24070777-S-000

The following products have been tested by us references to standards for electrical equipment designed for use within certain voltage limits in support of the Electrical Equipment (Safety) Regulations 2016 (S.I. 2016/1101). It is possible to use UKCA marking to demonstrative the Conformity with this Electrical Equipment (Safety) Regulations.

Applicant : Pihong Technology Co., Ltd.

Address : No. 568, Fuxing 3rd Rd., Guishan District,
Taoyuan City 333, Taiwan

Product : SWITCHING POWER SUPPLY

Trade Name : 

Model No. : PYA10xyzzzppp, PYA12xyzzzppp,
PYA15xyzzzppp, PYA10xyzzzpppQ,
PYA12xyzzzpppQ, PYA15xyzzzpppQ ("x", "y",
"zzz" and "ppp" are variables, see Table A for
details)

Test Standards :

BS EN IEC 62368-1:2020 +
A11:2020

Audio/video, information and
communication technology
equipment
Part 1: Safety requirements

Table A: Definition of variables:

Variable:	Range of variable:	Content:
x	E, K, T	Indicating one digit number to represent different plug type: E denotes European plug K denotes United Kingdom plug T denotes detachable plug, only for horizontal type enclosure
y	V or blank	Represents different shell type: V denotes vertical blank denotes Horizontal
zzz	050 to 300	'zzz' are 3 digits indicating 10 times the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc.
ppp	001 to 300	'ppp' are 3 digits indicating 100 times the output current value in A. For example, 001 represents the output current is 0.01A, 300 represents the output current is 3.0A.

Remarks:

The rated output current is rising in steps of 0.01A.

The rated output voltage is rising in steps of 0.1V.

Output voltage multiplied with output current are only tested up to the maximum output power.

The detachable plug portion can be European plug, United Kingdom plug.

When "x" = "T", "y" can only be "blank".

**UK
CA**



Toney Cao
Supervisor

Date: Sept. 28, 2024

The statement is based on a single evaluation of one sample of above mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab. logo.