

Certificate of Compliance

Certificate Number:

UL-US-2448955-0

Report Reference:

E127643-20241215

Issue Date:

2024-12-18

Issued to:

PHIHONG TECHNOLOGY CO LTD 568 Fu Xing 3rd Rd Guishan District Taoyuan 333611 Taiwan

This certificate confirms that representative samples of:

QQJQ - Power Supplies for Use with Audio/Video, Information and Communication Technology Equipment

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

UL 62368-1, 3rd Ed., Issue Date: 2019-12-13, Revision Date: 2021-10-22

Additional Information:

See UL Product iQ® at https://ig.ulprospector.com for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch

UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

Certificate number UL-US-2448955-0 Report reference E127643-20241215

Date 2024-12-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
PYA10xyzzzppp, x, A, or T, A means fixed US/Mexico plug provided, T means detachable plug provided, only for horizontal type enclosure. y, V or blank, Represents different shell types used: "V" means vertical and blank represents Horizontal. zzz, 050 to 300, "zzz' are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. ppp, 001 to 300, "ppp' are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 300 represents the output current is 3.0A.	Power Supplies for AV, ITE, and AVICT Equipment
PYA10xyzzzpppQ, x, A, or T, A means fixed US/Mexico plug provided, T means detachable plug provided, only for horizontal type enclosure. y, V or blank, Represents different shell types used: "V" means vertical and blank represents Horizontal. zzz, 050 to 300, "zzz' are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. ppp, 001 to 300, "ppp' are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 300 represents the output current is 3.0A.	Power Supplies for AV, ITE, and AVICT Equipment
PYA12xyzzzppp, x, A, or T, A means fixed US/Mexico plug provided, T means detachable plug provided, only for horizontal type enclosure. y, V or blank, Represents different shell types used: "V" means vertical and blank represents Horizontal. zzz, 050 to 300, "zzz' are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. ppp, 001 to 300, "ppp' are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 300 represents the output current is 3.0A.	Power Supplies for AV, ITE, and AVICT Equipment



Certificate number UL-US-2448955-0 Report reference E127643-20241215

Date 2024-12-18

PYA12xyzzzpppQ, x, A, or T, A means fixed US/Mexico plug provided, T means detachable plug provided, only for horizontal type enclosure. y, V or blank, Represents different shell types used: "V" means vertical and blank represents Horizontal. zzz, 050 to 300, "zzz' are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. ppp, 001 to 300, "ppp' are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 300 represents the output current is 3.0A.	Power Supplies for AV, ITE, and AVICT Equipment
PYA15xyzzzppp, x, A, or T, A means fixed US/Mexico plug provided, T means detachable plug provided, only for horizontal type enclosure. y, V or blank, Represents different shell types used: "V" means vertical and blank represents Horizontal. zzz, 050 to 300, "zzz' are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. ppp, 001 to 300, "ppp' are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 300 represents the output current is 3.0A.	Power Supplies for AV, ITE, and AVICT Equipment
PYA15xyzzzpppQ, x, A, or T, A means fixed US/Mexico plug provided, T means detachable plug provided, only for horizontal type enclosure. y, V or blank, Represents different shell types used: "V" means vertical and blank represents Horizontal. zzz, 050 to 300, "zzz' are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. ppp, 001 to 300, "ppp' are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 300 represents the output current is 3.0A.	Power Supplies for AV, ITE, and AVICT Equipment





Certificate of Compliance

Certificate Number:

UL-CA-2436990-0

Report Reference:

E127643-20241215

Issue Date:

2024-12-18

Issued to:

PHIHONG TECHNOLOGY CO LTD 568 Fu Xing 3rd Rd Guishan District Taoyuan 333611 Taiwan

This certificate confirms that representative samples of:

QQJQ7 - Power Supplies for Use with Audio/Video, Information and Communication Technology Equipment Certified for Canada

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

CSA C22.2 No. 62368-1:19, 3rd Ed., Issue Date: 2019-12-13, Revision Date: 2021-10-22

Additional Information:

See UL Product iQ® at https://iq.ulprospector.com for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch

UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

Certificate number UL-CA-2436990-0 Report reference E127643-20241215

Date 2024-12-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
PYA10xyzzzppp, x, A, or T, A means fixed US/Mexico plug provided, T means detachable plug provided, only for horizontal type enclosure. y, V or blank, Represents different shell types used: "V" means vertical and blank represents Horizontal. zzz, 050 to 300, "zzz' are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. ppp, 001 to 300, "ppp' are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 300 represents the output current is 3.0A.	Power Supplies for AV, ITE, and AVICT Equipment
PYA10xyzzzpppQ, x, A, or T, A means fixed US/Mexico plug provided, T means detachable plug provided, only for horizontal type enclosure. y, V or blank, Represents different shell types used: "V" means vertical and blank represents Horizontal. zzz, 050 to 300, "zzz' are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. ppp, 001 to 300, "ppp' are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 300 represents the output current is 3.0A.	Power Supplies for AV, ITE, and AVICT Equipment
PYA12xyzzzppp, x, A, or T, A means fixed US/Mexico plug provided, T means detachable plug provided, only for horizontal type enclosure. y, V or blank, Represents different shell types used: "V" means vertical and blank represents Horizontal. zzz, 050 to 300, "zzz' are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. ppp, 001 to 300, "ppp' are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 300 represents the output current is 3.0A.	Power Supplies for AV, ITE, and AVICT Equipment



Certificate number UL-CA-2436990-0 Report reference E127643-20241215

Date 2024-12-18

PYA12xyzzzpppQ, x, A, or T, A means fixed US/Mexico plug provided, T means detachable plug provided, only for horizontal type enclosure. y, V or blank, Represents different shell types used: "V" means vertical and blank represents Horizontal. zzz, 050 to 300, "zzz' are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. ppp, 001 to 300, "ppp' are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 300 represents the output current is 3.0A.	Power Supplies for AV, ITE, and AVICT Equipment
PYA15xyzzzppp, x, A, or T, A means fixed US/Mexico plug provided, T means detachable plug provided, only for horizontal type enclosure. y, V or blank, Represents different shell types used: "V" means vertical and blank represents Horizontal. zzz, 050 to 300, "zzz' are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. ppp, 001 to 300, "ppp' are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 300 represents the output current is 3.0A.	Power Supplies for AV, ITE, and AVICT Equipment
PYA15xyzzzpppQ, x, A, or T, A means fixed US/Mexico plug provided, T means detachable plug provided, only for horizontal type enclosure. y, V or blank, Represents different shell types used: "V" means vertical and blank represents Horizontal. zzz, 050 to 300, "zzz' are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. ppp, 001 to 300, "ppp' are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 300 represents the output current is 3.0A.	Power Supplies for AV, ITE, and AVICT Equipment

